



From perennial favourite to long-term runner

OUR DUPLEX UNITS COMPLI 1000 IM S1 OPERATION

Our sewage lifting stations are as varied as the requirements themselves. And yet they all have a lot in common: They are easy to operate and maintain, and are characterised by a high degree of connection flexibility.

NEW in the range are three sewage lifting stations from the Compli 1000 series, which operate in S1 mode (permanent running). They are used wherever large quantities of waste water are produced in addition to toilet waste water.

Field of application:


- Public indoor swimming pools
- Hotel facilities with swimming pools
- Incalculable waste water quantity

Technical features:

- High operation reliability due to S1 operation
- PE tank volume 117 l
-) Both pumps either switch alternately or work together at peak load
- Ready to plug in and easy to install
- Flexible connection
- Height-variable inlets
- Duplex swing-type check valve with large maintenance opening

Control unit:

- Comfortable and easy-to-use HighLogo microprocessor control
 - Graphic, illuminated LCD display
 - Run time monitoring
 - Event memory
 - Display of switch-on pulses, operating hours, service intervals, level indicator and much more
- Motor current monitoring
- Multilingual menu
- GSM (optional accessory)



The three new models:

Compli 1010/4 HL S1 - JP50838 Compli 1015/4 HL S1 - JP50839 Compli 1025/4 HL S1 - JP50840

