

BASICLOGO AD/BD

CONTROL UNITS AND COMPONENTS

- Proven and solid control technology
- User-friendly handling
- Expandable functions
- Large range of level controls
- Usable down to -20 °C without heating



DESCRIPTION

Electronic control unit for level control of one (AD) or two (BD) d.o.l. starting submersible pump(s).

The BasicLogo with the standard features meets all the necessary requirements for the reliable control of sewage pumps. It can be adapted to individual requirements and is suitable for use with both non explosion protected and explosion protected submersible pumps (AD/BD ...Ex types).

The control unit can be combined with a large variety of different level controls to suit the application concerned, and it is supplied with a buzzer as standard with a facility for off the line operation.

All AD/BD ...ExM control units have a run dry protection (DRP) and an integrated static air level control with two independently operating pressure switches, which ensure high operating safety and low maintenance and therefore lower costs. In addition, the control units have a facility to adjust the pump follow-up time and start-up delay after a power failure, thereby optimising the pressure drainage system.

All BD types (for two pumps) automatically start up pumps 1 and 2 alternately. The resting pump is switched on during peak load or fault. Alternative operation of the unit without peak load function is possible, but with automatic switchover to the standby pump in the event of a fault. Variegated automatic start delay time after a power failure to prevent extreme rushes of current.

The clear and robust design of the unit enables it to be used outdoors in an empty outdoor casing at temperatures as low as -20°C without the need for any heating.

Further accessories are available on request

BASICLOGO AD/BD

CONTROL UNITS AND COMPONENTS

ELECTRICAL DATA

Type of enclosure	IP 44
-------------------	-------

BASICLOGO AD/BD

Type	Code No.	Voltage	Motor protection	Pre-fuse	HxWxL [mm]
Control for 1 pump					
AD 00 E	JP00289	1/N/PE~230 V	-	16 A	270 x 250 x 155
AD 00	JP00311	3/PE~230/400 V	-	16 A	270 x 250 x 155
AD 25	JP00310	3/N/PE~230/400 V	2.4 ... 4 A	16 A	270 x 250 x 155
AD 46	JP14353	3/N/PE~230/400 V	4 ... 6 A	16 A	270 x 250 x 155
AD 610	JP14354	3/N/PE~230/400 V	6 ... 9 A	16 A	270 x 250 x 155
AD 910	JP47263	3/N/PE~230/400 V	9 ... 12 A	20 A	270 x 250 x 155
Control unit for 1 pump with ex-proof					
AD 4 XE	JP25901	1/N/PE~230 V	4 A	16 A	430 x 250 x 155
AD 8 XE	JP25902	1/N/PE~230 V	8 A	16 A	430 x 250 x 155
AD 23 X	JP09754	3/N/PE~230/400 V	1 ... 1.6 A	16 A	250 x 250 x 155
AD 25 X	JP09683	3/N/PE~230/400 V	2.4 ... 4 A	16 A	250 x 250 x 155
AD 46 X	JP14355	3/N/PE~230/400 V	4 ... 6 A	16 A	250 x 250 x 155
AD 610 X	JP14356	3/N/PE~230/400 V	6 ... 9 A	16 A	250 x 250 x 155
AD 910 X	JP47265	3/N/PE~230/400 V	9 ... 12 A	20 A	250 x 250 x 155
Control for 2 pumps					
BD 00 E	JP45735	1/N/PE~230 V	10 A	20 A	430 x 250 x 155
BD 610 EC	JP45743	1/N/PE~230 V	6.3 ... 10 A	20 A	430 x 250 x 155
BD 00	JP45993	1/N/PE~230 V	4 ... 6.3 A	16 A	430 x 250 x 155
BD 25	JP45737	3/N/PE~230/400 V	2.5 ... 4 A	16 A	430 x 250 x 155
BD 46	JP45739	3/N/PE~230/400 V	4 ... 6.3 A	20 A	430 x 250 x 155
BD 610	JP45741	3/N/PE~230/400 V	6.3 ... 10 A	25 A	430 x 250 x 155
BD 910	JP47264	3/N/PE~230/400 V	6.3 ... 10 A	25 A	430 x 250 x 155
Control unit for 2 pumps with ex-proof					
BD 23 X	JP09755	3/N/PE~230/400 V	1 ... 1.6 A	16 A	430 x 250 x 155
BD 25 X	JP09681	3/N/PE~230/400 V	2.5 ... 4 A	16 A	430 x 250 x 155
BD 46 X	JP14360	3/N/PE~230/400 V	4 ... 6.3 A	20 A	430 x 250 x 155
BD 610 X	JP14361	3/N/PE~230/400 V	6.3 ... 10 A	25 A	430 x 250 x 155
BD 910 X	JP47266	3/N/PE~230/400 V	6.3 ... 10 A	25 A	430 x 250 x 155

BASICLOGO AD/BD

CONTROL UNITS AND COMPONENTS

	Einzelanlagen					Doppelanlagen			
	AD 00 E	AD 00	AD 25, 46, 610, 910	AD 4 XE, 8 XE	AD 23 X, 25 X, 46 X, 610 X, 910 X	BD 00 E	BD 610 EC	BD 00, 25, 46, 610, 910	BD 23 X, 25 X, 46 X, 610 X, 910 X
Equipment									
Starting	direct	direct	direct	direct	direct	direct	direct	direct	direct
Motor contactor	1	1	1	1	1	2	2	2	2
Excess current relay			1		1				
Motor protection switch				1			2	2	2
Neozed fuse						2			
Motor capacitor				1			2		
A.C. power supply 230 V/2 A	1	1	1	1	1	1	1	1	1
Hand-Off-Automatic selector switch	1	1	1	1	1	2	2	2	2
Buzzer	1	1	1	1	1	1	1	1	1
Alarm reset button					1				1
Rreset button					1				1
Indicator lamp for operation	1	1	1	1	1	2	2	2	2
Indicator lamp for sense of rotation		1	1		1			1	1
Indicator lamp for high water alarm	1	1	1	1	1	1	1	1	1
Indicator lamp for malfunction pump			1	1	1		2	2	2
Indicator lamp for malfunction temp. limiter				1	1				2
Indicator lamp for water deficiency					1				1
Pot. free contact for collective fault	1	1	1	1	1	1	1	1	1
Watchdog timer 8.9 - 50.7 min.					1				1
Potential free contact, as before					1				1

	Code No.	Einzelanlagen			Doppelanlagen	
		AD 00 E	AD 00, 25, 46, 610, 910	AD 4 XE, 8 XE, 23 X, 25 X, 46 X, 610 X, 910 X	BD 00 E, 610 EC, 00, 25, 46, 610, 910	BD 23 X, 25 X, 46 X, 610 X, 910 X
Niveaugeber						
Subm. switch pack A	JP16718	1	1	1		
Subm. switch pack AmG	JP16719	2	1	1		
Subm. switch pack B	JP16725				1	1
Subm. switch pack BmG	JP16726				1	1
Auxiliary switch unit ExH-A	JP16720			1		
Auxiliary switch unit ExH-B for explosion-proof pumps only	JP00295					1
Luftmembranschaltung	JP01080	1	1	1	1	1
Hydrostat. Niveaugeber HD 04	JP44547	1	1		1	
Hydrostat. Niveaugeber HD 04 Ex	JP44548			1		1

BASICLOGO AD/BD

CONTROL UNITS AND COMPONENTS

	Code No.	Einzelanlagen						Doppelanlagen			
		AD 00 E, 00	AD 25, 46, 610, 910	AD 4 XE	AD 8 XE, 23 X	AD 25 X	AD 46 X, 610 X, 910 X	BD 00 E, 610 EC, 00, 25, 46, 610, 910	BD 23 X	BD 25 X	BD 46 X, 610 X, 910 X
Zubehör											
Dry run protection unmounted	JP41463					1	1		1	1	1
Dry run protection US_Ex	JP44603			1	1	1			1	1	
Rechargeable battery	JP44850	1	1	1	1	1	1	1	1	1	1
Retaining plate	JP50213	1	1		1	1	1	1	1	1	1
Zubehör werkseitig montiert											
Dry run protection	JP41881					1	1			1	1
LCD-Betriebsstundenzähler	JP23243	1	1	1	1	1	1	2	2	2	2