

# PENTAIR JUNG PUMPEN BASICLOGO

## CONTROL UNITS AND COMPONENTS

- Proven and solid control technology
- User-friendly handling
- Integrated standard functions optimised for requirements
- Expandable functions
- Usable down to -20 °C without heating
- Large range of level controls
- Functions optimised for pressure drainage systems



### OPIS

Electronic control unit for level control of one (AD) or two (BD) d.o.l. starting submersible pump(s).

The BasicLogo with the standard features meets all the necessary requirements for the reliable control of sewage pumps. It can be adapted to individual requirements and is suitable for use with both non explosion protected and explosion protected submersible pumps (AD/BD ...Ex types).

The control unit can be combined with a large variety of different level controls to suit the application concerned, and it is supplied with a buzzer as standard with a facility for off the line operation.

All AD/BD ...ExM control units have a run dry protection (DRP) and an integrated static air level control with two independently operating pressure switches, which ensure high operating safety and low maintenance and therefore lower costs. In addition, the control units have a facility to adjust the pump follow-up time and start-up delay after a power failure, thereby optimising the pressure drainage system.

All BD types (for two pumps) automatically start up pumps 1 and 2 alternately. The resting pump is switched on during peak load or fault. Alternative operation of the unit without peak load function is possible, but with automatic switchover to the standby pump in the event of a fault. Variegated automatic start delay time after a power failure to prevent extreme rushes of current.

The clear and robust design of the unit enables it to be used outdoors in an empty outdoor casing at temperatures as low as -20°C without the need for any heating.

# BASICLOGO

## CONTROL UNITS AND COMPONENTS

### DANE ELEKTRYCZNE

Rodzaj ochrony	IP 44
----------------	-------

### BASICLOGO

Typ	Nr kat.	Napięcie	Zabezpieczenie silnika	Vorsicherung	HxWxL [mm]
<b>Sterowanie dla 1 pompy</b>					
AD 00	<b>JP00311</b>	1/N/PE~230 V	-	16 A	270 x 250 x 155
AD 00 E	<b>JP00289</b>	3/N/PE~230/400 V	-	16 A	270 x 250 x 155
AD 25	<b>JP00310</b>	3/N/PE~230/400 V	2,4 ... 4 A	16 A	270 x 250 x 155
AD 46	<b>JP14353</b>	3/N/PE~230/400 V	4 ... 6 A	16 A	270 x 250 x 155
AD 610	<b>JP14354</b>	3/N/PE~230/400 V	6 ... 9 A	16 A	270 x 250 x 155
AD 910	<b>JP47263</b>	3/N/PE~230/400 V	9 ... 12 A	20 A	270 x 250 x 155
<b>Steuerung für 1 Pumpe mit Ex-Schutz</b>					
AD 4 XE	<b>JP25901</b>	1/N/PE~230 V	4 A	16 A	430 x 250 x 155
AD 8 XE	<b>JP25902</b>	1/N/PE~230 V	8 A	16 A	430 x 250 x 155
AD 23 X	<b>JP09754</b>	3/N/PE~230/400 V	1 ... 1,6 A	16 A	250 x 250 x 155
AD 25 X	<b>JP09683</b>	3/N/PE~230/400 V	2,4 ... 4 A	16 A	250 x 250 x 155
AD 46 X	<b>JP14355</b>	3/N/PE~230/400 V	4 ... 6 A	16 A	250 x 250 x 155
AD 610 X	<b>JP14356</b>	3/N/PE~230/400 V	6 ... 9 A	16 A	250 x 250 x 155
AD 910 X	<b>JP47265</b>	3/N/PE~230/400 V	9 ... 12 A	20 A	250 x 250 x 155
<b>Control unit for 1 MultiCut pump with integrated SD level control</b>					
AD 8 ExME, TLS	<b>JP43162</b>	1/N/PE~230 V	8 A	16 A	430 x 250 x 155
AD 12 ExME, TLS	<b>JP43163</b>	1/N/PE~230 V	12 A	16 A	430 x 250 x 155
AD 25 ExM, TLS	<b>JP43159</b>	3/N/PE~230/400 V	2,4 ... 4 A	16 A	430 x 250 x 155
AD 46 ExM, TLS	<b>JP43160</b>	3/N/PE~230/400 V	4 ... 6 A	16 A	430 x 250 x 155
AD 610 ExM, TLS	<b>JP43161</b>	3/N/PE~230/400 V	6 ... 9 A	16 A	430 x 250 x 155
<b>Sterowanie dla 2 pomp</b>					
BD 00	<b>JP45993</b>	1/N/PE~230 V	4 ... 6,3 A	16 A	430 x 250 x 155
BD 00 E	<b>JP45735</b>	3/N/PE~230/400 V	10 A	20 A	430 x 250 x 155
BD 25	<b>JP45737</b>	3/N/PE~230/400 V	2,5 ... 4 A	16 A	430 x 250 x 155
BD 46	<b>JP45739</b>	3/N/PE~230/400 V	4 ... 6,3 A	20 A	430 x 250 x 155
BD 610	<b>JP45741</b>	3/N/PE~230/400 V	6,3 ... 10 A	25 A	430 x 250 x 155
BD 610 EC	<b>JP45743</b>	1/N/PE~230 V	6,3 ... 10 A	20 A	430 x 250 x 155
BD 910	<b>JP47264</b>	3/N/PE~230/400 V	6,3 ... 10 A	25 A	430 x 250 x 155
<b>Steuerung für 2 Pumpen mit Ex-Schutz</b>					
BD 23 X	<b>JP09755</b>	3/N/PE~230/400 V	1 ... 1,6 A	16 A	430 x 250 x 155
BD 25 X	<b>JP09681</b>	3/N/PE~230/400 V	2,5 ... 4 A	16 A	430 x 250 x 155
BD 46 X	<b>JP14360</b>	3/N/PE~230/400 V	4 ... 6,3 A	20 A	430 x 250 x 155
BD 610 X	<b>JP14361</b>	3/N/PE~230/400 V	6,3 ... 10 A	25 A	430 x 250 x 155
BD 910 X	<b>JP47266</b>	3/N/PE~230/400 V	6,3 ... 10 A	25 A	430 x 250 x 155
<b>Control unit for 2 MultiCut pumps with integrated SD level control</b>					
BD 25 ExM, TLS	<b>JP43165</b>	3/N/PE~230/400 V	2,5 ... 4 A	16 A	430 x 250 x 155
BD 46 ExM, TLS	<b>JP43166</b>	3/N/PE~230/400 V	4 ... 6,3 A	20 A	430 x 250 x 155
BD 610 ExM, TLS	<b>JP43167</b>	3/N/PE~230/400 V	6,3 ... 10 A	25 A	430 x 250 x 155