

U5

DRAINAGE PUMPS

- Cooling jacket for motor housing
- Low level pumping by detachable strainer base
- NEW: Flushing device activatable and deactivatable
- Variable discharge branch with closable ventilation
- Safe to run dry
- 10/20 mm free passage with EIP technology
- Moisture sealed cable inlet
- NEW: Fluid temperature 35 °C, temporarily 60 °C (10 min.)



DESCRIPTION


The U5K(S) is an extremely powerful and versatile centrifugal submersible pump for both stationary and portable use. The pump is suitable for faecal-free wastewater with solids up to 10 mm particle size. Thanks to the removable strainer base, it is possible to increase the free passage to 20 mm.

Stationary in a basement chamber or a collecting tank, with an automatic switch attached, the U5K(S) handles all dirty water arising from domestic drainage sources such as washing machines, dishwashers, washstands, etc. Deposit accumulation in the reservoirs and chambers is reduced to a minimum by means of a flushing device.

Guide rail systems offer the advantages of quick and easy maintenance. The Easyfix installation sets are particularly convenient. They are pre-assembled ready to plug in and can be installed as single or duplex systems. If the sump or tank runs dry temporarily, the pump can be vented by providing a drill-hole in the spiral housing.

The U5K(S) can be used as a portable unit for dealing with dirty water from garden ponds, flooded cellars or discharge chambers in laundry rooms or storage rooms. Thanks to its shallow, built-in suction system, it can reduce residual water level to no more than a few millimeters.

PERFORMANCE



Type	Delivery head H [m]	1	2	3	4	5	6	7
U5K/U5KS	Flow rate Q [m³/h]	11.5	10.5	9.0	7.5	6.5	4.5	2.5

Specifications can be changed without notice. Performance subject to ISO 9906 tolerances.

The minimum flow velocity in the pressure piping must be 0.7 m/s according to EN 12056. This data is represented in the performance curve as a limit of application.



U5

DRAINAGE PUMPS

SCOPE OF SUPPLY

Pump ready for connection acc. to EN 12050 with 90°, 1¼" female connection elbow with integrated self-ventilation, cable and plug, S model with automatic level float switch.

MECHANICAL DATA

Pump	Vertical single-stage	Run dry protection	Yes
Free passage	20 mm	Shaft	Stainless steel
Bearing	Ball bearings, grease-lubricated	Impeller	Vortex impeller, GFK
Seal on motor side	Rotary shaft seal	Motor housing	Stainless steel
Oil chamber	Yes	Pump housing	GRP
Seal on medium side	2-fold rotary shaft seals	Submersible	Yes
		Pressure outlet	1 1/4"


ELECTRICAL DATA

Voltage	1/N/PE~230 V	Insulation class	B
Motor rating P1	0.52 kW	Winding thermostat	Yes
Motor rating P2	0.38 kW	Motor protection	Integrated
Current	2.3 A	Plug	Safety
Type of enclosure	IP 68		

U5


Type	Code No.	Power line	Wires	Weight
Without level control				
U5K, 10 m cable	JP50047	10m H05RN-F	3G0,75	4.7 kg
With built-in level control				
U5KS, 10 m cable	JP50046	10m H07RN-F	3G1,0	5.4 kg
U5KS, 4 m cable	JP50045	4m H05RN-F	3G0,75	4.5 kg

Dimensions and switching points U5KS (mm)



56509-00

Dimensions and switching points special float switch




56509-00

U5


DRAINAGE PUMPS

Dimensions and switching points float switch (mm)




56509-00

Dimensions and switching points GR 32 (mm)




56510-00

Example of single pump installation with GR



56511-00

Example of duplex installation




56512-00


U5

DRAINAGE PUMPS

Example of installation and dimensions Easyfix 32 Single



Example of installation and dimensions Easyfix 32 Duo (mm)



Single unit with GR: sump area min. 40x50 cm or Ø 50 cm
Single unit without GR: sump area min. 40x40 cm or Ø 40 cm

Duplex unit with GR: sump area min. 50x50 cm, Ø 60 cm
Duplex unit without GR: sump area min. 50x50, Ø 55 cm

Single unit Easyfix 32 Single: sump min. 30x40 cm, Ø 40 cm

Duplex unit Easyfix 32 Duo: sump min. 50x40 cm, Ø 55 cm

Duplex unit Easyfix 32 Duo with special float: sump min. 50x50 cm Ø 70 cm

In case of installation beneath the backpressure level the pressure tube must be taken in a loop over the local backup level acc. to EN 12056. Besides, it must be secured with an EN 12050-4-proofed swing-type check valve. Additionally we recommend an alarm system.

In accordance with EN 12056-4 section 5.1, it has a built-in automatic spare pump or a double attachment included, which ensures that sewage drainage is not interrupted.

Suspend control unit in a dry room


MECHANICAL ACCESSORY

				Code No.
	① Swing-type check valve			
	R32 EN 12050-4	1¼" (DN 32), PN 4	90x90 (HxB)	JP09739
	DR 40 EN 12050-4	1½" (DN 40), PN 4	200x280 (HxB)	JP09155
	Rubber flap DN32	for transportable use	35x35 (HxB)	JP50774
	② Stop valve	1¼" (DN 32), PN 16	110x60 (HxB)	JP44785
		brass, 1½" (DN 40), PN 16	125x60 (HxB)	JP44786
	③ Elastic connection	+ Hose band clamps, 1¼" (DN 32), PN 3	100x42 (HxD)	JP50901
	④ Hose coupling			
	Hose coupling	1¼" (DN 25) brass, for transportable use		JP50849
	Coupling Storz C	1 1/4" male thread		JP44780
	Coupling wrench			JP25708
	⑤ Pressure hose	15 m, synthetic, Ø 25 mm		JP50830
		12,5 m, synthetic, with coupling Storz C, Ø 38 mm		JP50298
	House connection	1¼" - 38/32/25		JP44209



U5

DRAINAGE PUMPS

MECHANICAL ACCESSORY

			Code No.
	6 Hose set	1 1/4" (DN32), 15 m PVC hose c/w elbow	JP43550
	7 Special float	for lower switching points (U5 and U6)	JP44207
		for narrow chambers (mind. 30x30 od Ø30 cm)	JP40856
	Float fixation	for continuous pump operation	JP42175
	8 Guide rail system	GR 32	JP44000
	Support for guide rail extension	ex 2 m sump depth, per m 1 piece	JP28314
	Easyfix 32 Single	ready-to-connect installation set	JP50308
	Easyfix 32 Duo	ready-to-connect installation set with control unit for duplex units	JP50307
	9 Connection kit	DN 32, with telescopic pressure pipe 30-90 cm	JP44609

ELECTRICAL ACCESSORY

			Code No.
	a Alarm unit		
	AG3	subm. ball contact switch, mains dependent, potential-free contact, 3 m cable	JP44891
	AG10	subm. ball contact switch, mains dependent, potential-free contact, 9.5 m cable	JP44892
	Washing machine stop		
	AW3	subm. ball contact switch, mains dependent, 3 m cable	JP44895
	b Control for duplex units		
	Control unit HIGHLOGO 2-00 E	230 V	JP47996
	Control unit BD 00 E	230 V, for pumps U3-U6, US 62-105, UV3, UV 300, 08/2 ME	JP45735
	Level control		
	Subm. switch pack B	3 subm. ball contact switch with 9.5 m and fixing devices	JP16725
	Subm. switch pack BmG	3 subm. ball contact switch with 9.5 m and counterweight	JP16726
	c Rechargeable battery	9 V, for mains independent alarm	JP44850
	d Smart Home	FTJP radio transmitter	JP47209